

LTR 6140T



LAMTRAC



LTR 6140T

+ DENIS CIMAF
DAF-180Di

Note: The specifications are given under ideal conditions and on the basis of adequate operator skill and ability.



Features

- Cummins QSB 4.5 Tier III
- Single Boom Arm
- 86% Peripheral Visibility
- Side Door Entry
- Double Escape Hatch (Ingress & Egress)

Dimensions

Track Width	450 mm	17.75"
Overall Length	3441 mm	135.5"
Overall Width	1848 mm	72.75"
Overall Height	2210 mm	87"
Ground Clearance	406 mm	16"
Ground Pressure (no attachment)	26.89 kPa	3.9 psi
Weight	6305 kg	13,900 lbs

Performance

Speed		
Variable Range	0-16 km/h	0-10 mph

Engine

Make	Cummins
Model	QSB 4.5
Displacement	4.5 L
Horsepower	140 hp (104 kW) @ 2000 RPM
Torque	457 ft·lbf (620 N·m) @ 1500 RPM

Tracks

Rubber Compound Track

Capacities

Fuel Tank	170 Liters	45 gallons
Hydraulic Tank	57 Liters	15 gallons

Electrical

Voltage		12 Volts
Battery Capacity	1500 CCA	310 RC@25 A
Alternator		160 A

Standard Equipment

- Air Conditioning
- Digital Dash Display
- Convenience 12 V Power Port
- Ingress & Egress Roof Escape
- Dome Light
- Joystick Controls
- Cab Heater / Defrost System/Air Conditioning
- Certified Cab - ROPS / FOPS / OPS

Optional Equipment

Forestry Package	Bucket, General Purpose	Power Box Rake
Large Capacity Fuel Tank	Bucket, Light Material	Snow Blade
Hydraulic Winch	Bucket, Multi-Purpose	Snow Blower
Rear View Camera	Brush Cutter, Rotary	Stump Grinder
Mulching Head	Dozer Blade	Trencher
Root Rake	Land Leveler	Vibratory Roller
Auger	Rotary Cutter	
Backhoe	Dozer Rake	
Broom, Rotary	Pallet Forks	

250 Exportation Street
Tracadie-Sheila, NB
Canada
E1X 1A2

Tel. 1.888.LAMTRAC
Fax. 506.393.8501
www.lamtrac.com